

App. No. 09/843,914

Art Unit 3762

P-8191.00

Claim Amendments

Please kindly make the following changes to the claims. Cancel claims 2. Amend claims 1, 8, 14, 20, 25, and 32.

Sub
B1
a1

1. *(currently amended)* A method for detecting a tachycardia, comprising:
sensing a heart rate;
comparing the heart rate to a heart rate threshold value;
initiating an adjustable number of intervals detected (NID) threshold upon detecting the heart rate greater than the heart rate threshold value;
resetting the adjustable NID threshold based on at least a first measurement of a hemodynamic parameter that identifies whether a tachycardia is a hemodynamic stable tachycardia or a non-hemodynamic stable tachycardia;
counting a consecutive number of intervals in which the heart rate is greater than the heart rate threshold value; ~~and~~
detecting ~~the~~ tachycardia if the consecutive number of intervals satisfies the adjustable NID threshold; ~~and~~
delivering a first therapy upon detection that the tachycardia that is hemodynamic stable tachycardia and a second therapy upon detection that the tachycardia that is non-hemodynamic stable tachycardia.

2. *(cancelled)*

3. *(original)* The method of claim 2, further comprising:
comparing a second heart rate to the heart rate threshold value after delivery of the first therapy;
resetting the adjustable NID threshold to a second adjustable NID threshold based on at least a second measurement of the hemodynamic parameter;
counting a consecutive number of intervals in which the second heart rate is greater than the heart rate threshold value; and

App. No. 09/843,914

Art Unit 3762

P-8191.00

delivering a second therapy if the consecutive number of intervals in which the second heart rate is greater than the heart rate threshold value satisfies the second adjustable NID threshold.

4. *(original)* The method of claim 1, further comprising storing one or more parameters relating to the tachycardia.
5. *(original)* The method of claim 1, wherein the hemodynamic parameter is blood pressure.
6. *(original)* The method of claim 5, wherein resetting the adjustable NID threshold comprises reducing the adjustable NID threshold in response to a drop in blood pressure.
7. *(original)* The method of claim 1, wherein the hemodynamic parameter is blood flow.
8. *(currently amended)* A method for detecting tachycardia, comprising:
initiating an adjustable number of intervals detected (NID) threshold upon detecting a heart rate greater than a heart rate threshold value;
resetting the adjustable NID threshold based on a physiologically-sensed condition to identify whether a tachycardia is a hemodynamic stable tachycardia or a non-hemodynamic stable tachycardia;
counting a consecutive number of intervals in which the heart rate is greater than the heart rate threshold value; ~~and~~
detecting tachycardia if the consecutive number of intervals is equal to or greater than the adjustable NID threshold; ~~and~~
delivering a first therapy upon detection that the tachycardia that is hemodynamic stable tachycardia and a second therapy upon detection that the tachycardia that is non-hemodynamic stable tachycardia.

App. No. 09/843,914

Art Unit 3762

P-8191.00

9. *(original)* The method of claim 8, further comprising delivering a first therapy upon detecting tachycardia.
10. *(original)* The method of claim 8, wherein detecting tachycardia comprises detecting ventricular tachycardia.
11. *(original)* The method of claim 8, wherein the physiologically-sensed condition is blood pressure.
12. *(original)* The method of claim 8, wherein the physiologically-sensed condition is blood flow.
13. *(original)* The method of claim 8, wherein resetting the adjustable NID threshold comprises modifying the adjustable NID threshold in accordance with a predetermined relationship between the physiologically-sensed condition and the NID threshold.
14. *(currently amended)* A method for detecting a cardiac event and delivering a therapy in response thereto, comprising:
- sensing at least one first R-R interval;
 - comparing the at least one first R-R interval to an interval threshold value;
 - initiating a first adjustable number of intervals detected (NID) threshold upon detecting the at least one first R-R interval less than the interval threshold value;
 - sensing a first hemodynamic measurement to identify whether a tachycardia is a hemodynamic stable tachycardia or a non-hemodynamic stable tachycardia;
 - resetting the first adjustable NID threshold based on the first hemodynamic measurement;
 - counting a first consecutive number of R-R intervals in which each of the first consecutive number of R-R intervals is less than the interval threshold value;
 - detecting tachycardia if the first consecutive number of R-R intervals is equal to or greater than the first adjustable NID threshold; and

App. No. 09/843,914

Art Unit 3762

P-8191.00

delivering a first therapy.

15. *(original)* The method of claim 14, further comprising:
sensing at least one second R-R interval;
comparing the at least one second R-R interval to the interval threshold value;
initiating a second adjustable number of intervals detected (NID) threshold upon
detecting the at least one second R-R interval less than the interval threshold value;
sensing a second hemodynamic measurement;
resetting the second adjustable NID threshold based on the second hemodynamic
measurement;
counting a second consecutive number of R-R intervals in which each of the second
consecutive number of R-R intervals is less than the interval threshold value;
detecting tachycardia if the second consecutive number of intervals is equal to or
greater than the second adjustable NID threshold; and
delivering a second therapy.
16. *(original)* The method of claim 15, further comprising storing one or more parameters
relating to the tachycardia.
17. *(original)* The method of claim 15, wherein one or both of the first and second
hemodynamic measurements is a blood pressure measurement.
18. *(original)* The method of claim 15, wherein one or both of the first and second
hemodynamic measurements is a blood flow measurement.
19. *(original)* The method of claim 17, wherein resetting one or both of the first
adjustable NID threshold and second adjustable NID threshold comprises reducing the first
adjustable NID threshold and second adjustable NID threshold in response to a drop in blood
pressure.

App. No. 09/843,914

Art Unit 3762

P-8191.00

20. *(currently amended)* A pacing apparatus, comprising:
sensing and pacing circuitry for sensing cardiac activity and generating pacing pulses;
a hemodynamic sensor; and
controller circuitry in communication with the hemodynamic sensor, the controller circuitry operable to:

sense a heart rate using the sensing and pacing circuitry;
compare the heart rate to a heart rate threshold value;
initiate an adjustable number of intervals detected (NID) threshold upon detecting the heart rate greater than the heart rate threshold value;
reset the adjustable NID threshold based on at least a first measurement of a hemodynamic parameter to identify whether a tachycardia is a hemodynamic stable tachycardia or a non-hemodynamic stable tachycardia;
count a consecutive number of intervals in which the heart rate is greater than the heart rate threshold value; and
detect tachycardia if the consecutive number of intervals satisfies the adjustable NID threshold; and
delivering a first therapy upon detection that the tachycardia is hemodynamic stable tachycardia and a second therapy upon detection that the tachycardia that is non-hemodynamic stable tachycardia.

21. *(original)* The pacing apparatus of claim 20, wherein the sensing and pacing circuitry is further operable to deliver a first therapy upon detection of tachycardia.

22. *(original)* The pacing apparatus of claim 20, wherein the hemodynamic sensor is a blood pressure sensor.

23. *(original)* The pacing apparatus of claim 20, wherein the hemodynamic sensor is a blood flow rate sensor.

24. *(original)* The pacing apparatus of claim 20, wherein the pacing apparatus is a PCD.

App. No. 09/843,914

Art Unit 3762

P-8191.00

25. *(currently amended)* A pacing apparatus, comprising:
sensing and pacing circuitry for sensing cardiac activity and generating pacing pulses;
a hemodynamic sensor; and
controller circuitry in communication with the hemodynamic sensor, the controller circuitry operable to:

initiate an adjustable number of intervals detected (NID) threshold
upon detecting a heart rate greater than a heart rate threshold value;

reset the adjustable NID threshold based on a physiologically-sensed
condition to identify whether a tachycardia is a hemodynamic stable tachycardia or a
non-hemodynamic stable tachycardia;

count a consecutive number of intervals in which the heart rate is
greater than the heart rate threshold value; and

detect tachycardia if the consecutive number of intervals is equal to or
greater than the adjustable NID threshold.

26. *(original)* The pacing apparatus of claim 25, wherein the sensing and pacing circuitry is further operable to deliver a first therapy upon detection of tachycardia.

27. *(original)* The pacing apparatus of claim 25, wherein the hemodynamic sensor is a blood pressure sensor.

28. *(original)* The pacing apparatus of claim 25, wherein the hemodynamic sensor is a blood flow rate sensor.

29. *(original)* The pacing apparatus of claim 25, wherein the physiologically-sensed condition is blood pressure.

30. *(original)* The pacing apparatus of claim 25, wherein the physiologically-sensed condition is blood flow.

App. No. 09/843,914

Art Unit 3762

P-8191.00

31. *(original)* The pacing apparatus of claim 25, wherein the pacing apparatus is a PCD.
32. *(currently amended)* A pacing apparatus, comprising:
sensing and pacing circuitry for sensing cardiac activity and generating pacing pulses;
a hemodynamic sensor; and
controller circuitry in communication with the hemodynamic sensor, the controller circuitry operable to:
- sense at least one first R-R interval;
 - compare the at least one first R-R interval to an interval threshold value;
 - initiate a first adjustable number of intervals detected (NID) threshold upon detecting the at least one first R-R interval less than the interval threshold value;
 - sense a first hemodynamic measurement to identify whether a tachycardia is a hemodynamic stable tachycardia or a non-hemodynamic stable tachycardia;
 - reset the first adjustable NID threshold based on the first hemodynamic measurement;
 - count a first consecutive number of R-R intervals in which each of the first consecutive number of R-R intervals is less than the interval threshold value;
 - detect tachycardia if the first consecutive number of R-R intervals is equal to or greater than the first adjustable NID threshold; and
 - deliver a first therapy.
33. *(original)* The pacing apparatus of claim 32, wherein the controller circuitry is further operable to:
- sense at least one second R-R interval;
 - compare the at least one second R-R interval to the interval threshold value;
 - initiate a second adjustable number of intervals detected (NID) threshold upon detecting the at least one second R-R interval less than the interval threshold value;

App. No. 09/843,914

Art Unit 3762

P-8191.00

sense a second hemodynamic measurement;
reset the second adjustable NID threshold based on the second hemodynamic measurement;
count a second consecutive number of R-R intervals in which each of the second consecutive number of R-R intervals is less than the interval threshold value;
detect tachycardia if the second consecutive number of R-R intervals is equal to or greater than the second adjustable NID threshold; and
deliver a second therapy.

34. *(original)* The pacing apparatus of claim 32, wherein the hemodynamic sensor is a blood pressure sensor.

35. *(original)* The pacing apparatus of claim 32, wherein the hemodynamic sensor is a blood flow rate sensor.

36. *(original)* The pacing apparatus of claim 32, wherein the pacing apparatus is a PCD.